## A Identification

· Product identifier

· Trade name; ASPHALT SOLUTIONS CHERRY 50% S

· Article number: 180110

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Flavorchem Corporation 1525 Brook Drive Downers Grove, IL 60515 USA 800.435.2867

· Information department: Regulatory department

Emergency telephone number:

During normal opening times: Call Chemtrec Day or Night

Domestic North America 800.424.9300/International 703.527.3887 (Collect calls accepted)

## 2 Hazard(s) identification

Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



Acute Tox. 4 H302 Harmful if swallowed.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labeling: benzaldehyde vanillin

(Contd. on page 2)

Reviewed on 07/12/2016

#### ande name: ASPHALT SOLUTIONS CHERRY 50% S

(Contd. of page 1)

#### · Hazard statements

Flammable liquid and vapor.

Harmful if swallowed.

### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

Rinse mouth.

*In case of fire: Use for extinction: CO2, powder or water spray.* 

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



1 Health = 1Fire = 2

REACTIVITY  $\bigcirc$  Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

#### ade name: ASPHALT SOLUTIONS CHERRY 50% S

(Contd. of page 2)

100-52-7	benzaldehyde		
	♠ Acute Tox. 4, H302; Flam. Liq. 4, H227		
628-63-7	pentyl acetate	2.5-<10%	
	🕸 Flam. Liq. 3, H226		
105-54-4	ETHYL BUTYRATE	2.5-<10%	
	Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335-H336		
121-33-5	vanillin	0.1-<2.5%	
	<b>♦</b> Acute Tox. 4, H302	"	
77-83-8	Aldehyde C-16	0.1-<2.5%	
	♠ Flam. Liq. 3, H226; ♠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335		

### 4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

· US

Reviewed on 07/12/2016

... ade name: ASPHALT SOLUTIONS CHERRY 50% S

(Contd. of page 3)

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in tightly sealed containers in a cool, dry place that is well ventilated. Away from heat, spark, and open flame.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

(Contd. on page 5)

ade name: ASPHALT SOLUTIONS CHERRY 50% S

		(Contd. of page 4
100-52	2-7 benzaldehyde	
WEEL	Short-term value: 4 ppm Long-term value: 2 ppm DSEN	
628-63	3-7 pentyl acetate	
PEL	Long-term value: 525 mg/m³, 100 ppm	
REL	Long-term value: 525 mg/m³, 100 ppm	
TLV	Short-term value: 532 mg/m³, 100 ppm Long-term value: 266 mg/m³, 50 ppm	
121-33	3-5 vanillin	
WEEL	Long-term value: 10 mg/m³	
WEEL		7

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

-US