Honeywell

Honeywell Titan® 7686

000000013894

Version 1.5

Revision Date 06/26/2014

Print Date 09/14/2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name

Honeywell Titan® 7686

MSDS Number

000000013894

Product Use Description

Polymer for Asphalt Modification

Manufacturer or supplier's

details

Honeywell International Inc.

115 Tabor Road

Morris Plains, NJ 07950-2546

For more information call

1-888 245-4738

+1-973-455-2145

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call:

Medical: 1-800-498-5701 or +1-303-389-1414

Transportation (CHEMTREC): 1-800-424-9300 or +1-703-

527-3887

(24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form

: Wax like solid pellets or powder

Color

: white

Odor

: Wax like mild

Classification of the substance or mixture

Classification of the

: Combustible dust

substance or mixture

GHS Label elements, including precautionary statements

Honeywell

Honeywell Titan® 7686

000000013894

Revision Date 06/26/2014 Version 1.5 Print Date 09/14/2016

Signal word : Warning

Hazard statements : May form combustible dust concentrations in air

Precautionary statements : Prevention:

Use personal protective equipment as required.

Hazards not otherwise

classified

: Product dust may be irritating to eyes, skin and respiratory

system.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Substance

Chemical Name CAS-No. Concentration 100.00 % Proprietary ingredient(s)

SECTION 4. FIRST AID MEASURES

Inhalation : Remove to fresh air. Call a physician if irritation develops or

persists.

Skin contact : Wash off with soap and water. Call a physician if irritation

> develops or persists. Cool skin rapidly with cold water after contact with molten material. Do not peel solidified product off

the skin. Call a physician immediately.

Rinse with plenty of water. Call a physician if irritation develops Eye contact

or persists.

Unlikely route of exposure. If swallowed, rinse mouth with Ingestion

water (only if the person is conscious). Never give anything by

mouth to an unconscious person. Do NOT induce vomiting.

Page 2 / 13

Honeywell

Honeywell Titan® 7686 00000013894

Version 1.5

Revision Date 06/26/2014

Print Date 09/14/2016

Consult a physician if necessary.

Notes to physician

Treatment

: Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water mist Dry chemical

Carbon dioxide (CO2)

Foam

Do not use a solid water stream as it may scatter and spread

fire.

Specific hazards during

firefighting

: Avoid dust formation.

Airborne dusts of this product in an enclosed space and in the

presence of an ignition source may constitute an explosion

hazard.

Risks of ignition followed by flame propagation or secondary explosions shall be prevented by avoiding accumulation of

dust, e.g. on floors and ledges.

Static charges on powders or powders in liquids may ignite

combustible atmospheres.

Watch footing on floors and stairs because of possible

spreading of molten material.

Material can create slippery conditions.

In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

Special protective equipment

for firefighters

: In the event of fire and/or explosion do not breathe fumes. Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Honeywell

Honeywell Titan® 7686

000000013894

Version 1.5

Revision Date 06/26/2014

Print Date 09/14/2016

Personal precautions

Wear personal protective equipment. Evacuate personnel to safe areas. Provide adequate ventilation.

May form explosive dust-air mixture.

Avoid dust formation.

Accumulations of dust from this product in the workplace may

increase the likelihood or severity of an explosion.

Risks of ignition followed by flame propagation or secondary explosions shall be prevented by avoiding accumulation of

dust, e.g. on floors and ledges.

Eliminate all ignition sources if safe to do so.

Do not swallow. Avoid breathing dust.

Avoid contact with skin, eyes and clothing.

Environmental precautions

Should not be released into the environment.

Prevent product from entering drains.

Methods for cleaning up

Avoid dust formation and electrical charging (sparking)

because dust explosion might occur.

Do not create a powder cloud by using a brush or compressed

air.

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Use only non-sparking tools.

For molten product:

If material is molten, allow to cool. Use caution, as material

may still be hot after solidification.

Spilled material will solidify.

Allow to solidify. Scrape up.

Shovel into suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Handling

Handling

: Wear personal protective equipment.

Avoid dust formation.

Floors, walls and other surfaces must be regularly cleaned. The material can accumulate static charge and can therefore

cause electrical ignition.

Static charges on powders or powders in liquids may ignite

Honeywell

Honeywell Titan® 7686

000000013894

Version 1.5

Revision Date 06/26/2014

Print Date 09/14/2016

combustible atmospheres.

Take precautionary measures against static discharges.

Material can create slippery conditions.

Do not swallow. Avoid breathing dust.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

All combustible solids have the potential to create a dust explosion hazard. The likelihood of an explosion can be dependent upon many factors, such as the explosive characteristics of the material, the design of the facility, and the

characteristics of the material, the design of the facility, and the manner in which the material is handled. A more detailed discussion can be found in NFPA Bulletin 654, "Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible

Particulate Solids."

Storage

Requirements for storage areas and containers

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Keep away from heat and sources of ignition.

Keep away from direct sunlight. Protect from physical damage. Do not store together with: Strong oxidizing agents

Amines

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures

Ensure that eyewash stations and safety showers are close to

the workstation location.

Do not swallow. Avoid breathing dust.

Avoid contact with skin, eyes and clothing.

Engineering measures

Use adequate ventilation and/or engineering controls in high

temperature processing to prevent exposure to vapours.

Provide exhaust ventilation if dust is formed.

Use only in an area equipped with explosion proof exhaust

ventilation.

Electrical equipment should be protected to the appropriate

Page 5 / 13

Honeywell

Honeywell Titan® 7686

00000013894

Version 1.5 Revision Date 06/26/2014 Print Date 09/14/2016

standard.

If formation of dust is observed, equipment has to be switched

off, cleaned and serviced.

Eye protection : Wear as appropriate:

Safety glasses with side-shields

For molten product:

Goggles or face shield, giving complete protection to eyes

Hand protection : When handling hot material, use heat resistant gloves.

Skin and body protection : Wear heat protective clothing for handling hot material.

Respiratory protection : In case of insufficient ventilation wear suitable respiratory

equipment.

Use NIOSH approved respiratory protection.

Hygiene measures : Wash hands before breaks and at the end of workday.

Remove and wash contaminated clothing before re-use.

Keep working clothes separately.

Exposure Guidelines

Components	Ask	CAS-No.	Value	Control parameters	Upda te	Basis
Particulates Not Otherwise Regulated			TWA : time weighted average	10 mg/m3	2008	ACGIH:US. ACGIH Threshold Limit Values
Further information	•	Form of exposure	: Inhalable	particles.		
Dorticulates Not			Ι τιλ/ Λ ·	2 ma/m2	2009	ACCIDIDE ACCID

Particulates Not		TWA:	3 mg/m3	2008	ACGIH:US. ACGIH
Otherwise		time	N		Threshold Limit
Regulated		weighted			Values
		average			
Further :	Form of exposure	: Respirable	particles.		•

Particulates Not	PEL	: 15 mg/m3	02	OSHA TRANS:US.
Otherwise	Perm		2006	OSHA Table Z-1
Regulated	ble			Limits for Air
	expos	sure		Contaminants (29
	limit	20.0		CFR 1910.1000)
				0111101011000)

Honeywell

Honeywell Titan® 7686 000000013894

Version 1.5

Revision Date 06/26/2014

Print Date 09/14/2016

Further information	:	Form of exposure	e : Total dust	•)		
Particulates No Otherwise Regulated	ot		PEL: Permissi ble exposure limit	5 mg/m3	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Further information	:	Form of exposure	e : Respirable	fraction.		-
Particulates No Otherwise Regulated	ot		TWA : time weighted average	15 mg/m3	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
Further information	:	Form of exposure	e : Total dust			
Particulates No Otherwise Regulated	ot		TWA : time weighted average	5 mg/m3	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
Further information	:	Form of exposure	: Respirable	fraction.		
Particulates No Otherwise Regulated			TWA : time weighted average	15 mg/m3	2000	Z3:US. OSHA Table Z-3 (29 CFR 1910.1000)
Further information		Form of exposure	: Total dust.			
Particulates No Otherwise Regulated	ot		TWA: time weighted average	5 mg/m3	2000	Z3:US. OSHA Table Z-3 (29 CFR 1910.1000)
Further information	:	Form of exposure		fraction.		

Honeywell

Honeywell Titan® 7686

000000013894

Version 1.5

Revision Date 06/26/2014

Print Date 09/14/2016

Particulates No Otherwise Regulated	t		TWA : time weighted average	50 millions of particles per cubic foot of air	2000	Z3:US. OSHA Table Z-3 (29 CFR 1910.1000)
Further information	:	Form of exposure	: Total dust			
Particulates No	t		TWA:	15 millions of	2000	Z3:US. OSHA Table

Particulates Not Otherwise Regulated		TWA : time weighted average	15 millions of particles per cubic foot of air	2000	Z3:US. OSHA Table Z-3 (29 CFR 1910.1000)
Further : information	Form of exposure	: Respirable	fraction.		

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state

: Wax like solid pellets or powder

Color

: white

Odor

: Wax like mild

рΗ

: Note: not applicable

Melting point/freezing point

: 88 - 140 °C

Boiling point/boiling range

: Note: not determined

Flash point

: > 491 °F (255 °C) Method: closed cup

Lower explosion limit

: Note: not applicable

Upper explosion limit

: Note: not applicable

Honeywell

Honeywell Titan® 7686

00000013894

Version 1.5

Revision Date 06/26/2014

Print Date 09/14/2016

Vapor pressure

: Note: not applicable

Vapor density

: Note: not applicable, (Air = 1.0)

Density

: 0.85 - 1.00 g/cm3

Water solubility

: Note: negligible

Ignition temperature

: Note: not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability

: Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Hazardous polymerisation does not occur.

Conditions to avoid

: Heat, flames and sparks.

Avoid dust formation and electrical charging (sparking)

because dust explosion might occur.

Avoid exposure to temperatures exceeding recommended processing conditions. Honeywell should be contacted if questions arise concerning specific processing conditions.

Incompatible materials to

avoid

: Strong oxidizing agents

Amines

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

Honeywell

Honeywell Titan® 7686 000000013894

Print Date 09/14/2016 Version 1.5 Revision Date 06/26/2014

DOT Not dangerous goods

TDG Not dangerous goods

Not dangerous goods IATA

IMDG Not dangerous goods

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances

Control Act

: On the inventory, or in compliance with the inventory

Australia. Industrial Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL)

: On the inventory, or in compliance with the inventory

Japan. Kashin-Hou Law

List

: On the inventory, or in compliance with the inventory

Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control

: On the inventory, or in compliance with the inventory

Act

China. Inventory of Existing Chemical Substances

: On the inventory, or in compliance with the inventory

NZIOC - New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

Honeywell

Honeywell Titan® 7686

000000013894

Version 1.5

Revision Date 06/26/2014

Print Date 09/14/2016

SARA 302 Components

: SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 Components

: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

SARA 311/312 Hazards

: No SARA Hazards

California Prop. 65

: This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

WHMIS Classification

: Not Rated

This product has been classified according to the hazard criteria

of the CPR and the MSDS contains all of the information

required by the CPR.

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 0	0
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

Honeywell

Honeywell Titan® 7686 00000013894

Version 1.5

Revision Date 06/26/2014

Print Date 09/14/2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 01/23/2014

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group



HONEYWELL 7686, 25 KG, BAG

Version 1

Revision Date 02/01/2010

Print Date 02/19/2010

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name

Honeywell 7686

MSDS Number

000000013894

Product Use Description

Polymer, Lubricant

Company

Honeywell International, Inc.

101 Columbia Road

Morristown, NJ 07962-1057

For more information call

1-888 245-4738

1-973-455-2145

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call

Medical: 1-800-498-5701

Transportation: 1-800-424-9300 or +1-703-527-3887

(24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form

: Wax like solid pellets or powder

Color

: white

Odor

: Wax like mild

Hazard Summary

: May form combustible dust - air mixtures. During processing, dust may form explosive mixture in air. Accumulations of dust from this product in the workplace may increase the likelihood or severity of an explosion. Static charges on powders or powders in liquids may ignite combustible atmospheres. Product dust may be irritating to eyes, skin and respiratory system. Thermal decomposition can lead to release of irritating gases and vapours. The molten product can cause

serious burns.

Potential Health Effects

Skin

: May cause mechanical irritation.

The molten product can cause serious burns.

Eyes

May cause mechanical irritation.

Thermal decomposition can lead to release of irritating gases

and vapours.



HONEYWELL 7686, 25 KG, BAG

Version 1

Revision Date 02/01/2010

Print Date 02/19/2010

Ingestion

: Unlikely route of exposure.

No known effect.

Inhalation

: May cause mechanical irritation.

Thermal decomposition can lead to release of irritating gases

and vapours.

Chronic Exposure

: None known.

Aggravated Medical

Condition

: None known.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component

CAS-No.

Weight percent

Oxidized Polyethylene

68441-17-8

100.00

SECTION 4. FIRST AID MEASURES

Inhalation

: Remove to fresh air. Call a physician if irritation develops or

persists.

Skin contact

: Wash off with soap and water. Call a physician if irritation develops or persists. Cool skin rapidly with cold water after

contact with molten material. Do not peel solidified product off

the skin. Call a physician immediately.

Eye contact

: Rinse with plenty of water. Call a physician if irritation develops

or persists.

Ingestion

: Unlikely route of exposure. If swallowed, rinse mouth with

water (only if the person is conscious). Never give anything by mouth to an unconscious person. Do NOT induce vomiting.

Consult a physician if necessary.

Notes to physician

Treatment

: Treat symptomatically.



HONEYWELL 7686, 25 KG, BAG

Version 1

Revision Date 02/01/2010

Print Date 02/19/2010

SECTION 5. FIRE-FIGHTING MEASURES

Flash point

: >255 °C (491 °F)

closed cup

Lower explosion limit

: not applicable

Upper explosion limit

: not applicable

Suitable extinguishing

media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water mist Dry chemical

Carbon dioxide (CO2)

Foam

Do not use a solid water stream as it may scatter and spread

fire.

Specific hazards during fire

fighting

Avoid dust formation.

Airborne dusts of this product in an enclosed space and in the

presence of an ignition source may constitute an explosion

hazard.

Risks of ignition followed by flame propagation or secondary

explosions shall be prevented by avoiding accumulation of

dust, e.g. on floors and ledges.

Static charges on powders or powders in liquids may ignite

combustible atmospheres.

Watch footing on floors and stairs because of possible

spreading of molten material.

Material can create slippery conditions.

In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

Special protective equipment for fire-fighters

In the event of fire and/or explosion do not breathe fumes. Wear self-contained breathing apparatus and protective suit.

Additional advice

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions

: Wear personal protective equipment.

Evacuate personnel to safe areas.

Provide adequate ventilation.

May form explosive dust-air mixture.



HONEYWELL 7686, 25 KG, BAG

Version 1

Revision Date 02/01/2010

Print Date 02/19/2010

Avoid dust formation.

Accumulations of dust from this product in the workplace may

increase the likelihood or severity of an explosion.

Risks of ignition followed by flame propagation or secondary explosions shall be prevented by avoiding accumulation of

dust, e.g. on floors and ledges.

Eliminate all ignition sources if safe to do so.

Do not swallow. Avoid breathing dust.

Avoid contact with skin, eyes and clothing.

Environmental precautions

Should not be released into the environment.

Prevent product from entering drains.

Methods for cleaning up

: Avoid dust formation and electrical charging (sparking)

because dust explosion might occur.

Do not create a powder cloud by using a brush or compressed

air

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Use only non-sparking tools.

For molten product:

If material is molten, allow to cool. Use caution, as material

may still be hot after solidification.

Spilled material will solidify.

Allow to solidify. Scrape up.

Shovel into suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Handling

Handling

: Wear personal protective equipment.

Avoid dust formation.

Floors, walls and other surfaces must be regularly cleaned. The material can accumulate static charge and can therefore

cause electrical ignition.

Static charges on powders or powders in liquids may ignite

combustible atmospheres.

Take precautionary measures against static discharges.

Material can create slippery conditions.

Do not swallow. Avoid breathing dust.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

All combustible solids have the potential to create a dust explosion hazard. The likelihood of an explosion can be



HONEYWELL 7686, 25 KG, BAG

Version 1

Revision Date 02/01/2010

Print Date 02/19/2010

dependent upon many factors, such as the explosive characteristics of the material, the design of the facility, and the manner in which the material is handled. A more detailed discussion can be found in NFPA Bulletin 654, "Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids."

Storage

Requirements for storage areas and containers

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Keep away from heat and sources of ignition.

Keep away from direct sunlight. Protect from physical damage. Do not store together with: Strong oxidizing agents

Amines

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures

: Ensure that eyewash stations and safety showers are close to

the workstation location.

Do not swallow. Avoid breathing dust.

Avoid contact with skin, eyes and clothing.

Engineering measures

Use adequate ventilation and/or engineering controls in high

temperature processing to prevent exposure to vapors.

Provide exhaust ventilation if dust is formed.

Use only in an area equipped with explosion proof exhaust

ventilation.

Electrical equipment should be protected to the appropriate

standard.

If formation of dust is observed, equipment has to be switched

off, cleaned and serviced.

Eye protection

Wear as appropriate:

Safety glasses with side-shields

For molten product:

Goggles or face shield, giving complete protection to eyes

Hand protection

When handling hot material, use heat resistant gloves.

Skin and body protection

Wear heat protective clothing for handling hot material.

Respiratory protection

: In case of insufficient ventilation wear suitable respiratory

Page 5 / 10



HONEYWELL 7686, 25 KG, BAG

Version 1

Revision Date 02/01/2010

Print Date 02/19/2010

equipment.

Use NIOSH approved respiratory protection.

Hygiene measures

Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

Keep working clothes separately.

Exposure Guidelines

Particulates Not Otherwise Regulated **ACGIH**

TWA

10 mg/m3

Form of exposure

Inhalable particles.

ACGIH

TWA

3 mg/m3

Form of exposure

Respirable particles.

OSHA Z1 PEL 5 mg/m3

Form of exposure Respirable fraction. All inert or nuisance dusts, whether mineral, inorganic, or organic, not listed specifically by substance name are covered by the Particulates Not Otherwise Regulated (PNOR) limit which is the same as the inert or nuisance dust limit of Table Z-3.

OSHA Z1 PEL

15 mg/m3

Form of exposure Total dust. All inert or nuisance dusts, whether mineral, inorganic, or organic, not listed specifically by substance name are covered by the Particulates Not Otherwise Regulated (PNOR) limit which is the same as the inert or nuisance dust limit of Table Z-3.

OSHA Z1A

TWA

5 mg/m3

Form of exposure

Respirable fraction.

OSHA Z1A **TWA**

15 mg/m3

Total dust. Form of exposure

Z3

TWA

TWA

15 millions of particles per cubic foot of air

Form of exposure

Respirable fraction.

Z3

50 millions of particles

per cubic foot of air

Form of exposure

Total dust.

Z3

TWA

5 mg/m3

Form of exposure

Respirable fraction.



HONEYWELL 7686, 25 KG, BAG

Version 1

Revision Date 02/01/2010

Print Date 02/19/2010

Z3

TWA

15 mg/m3

Form of exposure

Total dust.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form

: Wax like solid pellets or powder

Color

: white

Odor

: Wax like mild

pH

: not applicable

Melting point/range

: 88 - 140 °C (190 - 284 °F)

Boiling point/boiling range

: not determined

Vapor pressure

: not applicable

Relative vapour density

: not applicable, (Air = 1.0)

Density

: 0.85 - 1.00 g/cm3

Water solubility

: negligible

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid

: Heat, flames and sparks.

Avoid dust formation and electrical charging (sparking)

because dust explosion might occur.

Avoid exposure to temperatures exceeding recommended processing conditions. Honeywell should be contacted if questions arise concerning specific processing conditions.

Materials to avoid

: Strong oxidizing agents

Amines

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide

Carbon dioxide (CO2)

Hazardous reactions

: Hazardous polymerisation does not occur.

Stable under recommended storage conditions.



HONEYWELL 7686, 25 KG, BAG

Version 1

Revision Date 02/01/2010

Print Date 02/19/2010

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

: LD50 rat

Dose: > 2,500 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Additional ecological

information

: Not inherently biodegradable.

We have no quantitative data concerning the ecological effects

of this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Information: Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

DOT

Not dangerous goods

TDG

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances

Control Act

: On the inventory, or in compliance with the inventory

Australia. Industrial

Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection

Act (CEPA). Domestic Substances List (DSL).

: On the inventory, or in compliance with the inventory



HONEYWELL 7686, 25 KG, BAG

Version 1

Revision Date 02/01/2010

Print Date 02/19/2010

(Can. Gaz. Part II, Vol. 133)

Japan. Kashin-Hou Law

List

: On the inventory, or in compliance with the inventory

Korea. Toxic Chemical Control Law (TCCL) List

: On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act

: On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances

: On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

SARA 311/312 Hazards

: No SARA Hazards

California Prop. 65

: This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

WHMIS Classification

: Not Rated

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information

required by the CPR.



HONEYWELL 7686, 25 KG, BAG

Version 1

Revision Date 02/01/2010

Print Date 02/19/2010

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 0	0
Flammability	: 1	1
Physical Hazard	: 0	
Instability	3	0