Safety Data Sheet

ocording to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

#### 6.4. Reference to other sections

See also sections 8 and 13.

#### SECTION 7: Handling and Storage

#### 7.1. Precautions for safe handling

Precautions for safe handling

: Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

#### Conditions for safe storage, including any incompatibilities 7.2.

Storage conditions

: Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

#### 7.3. Specific end use(s)

None,

## SECTION & Exposure controls/personal protection.

#### 8.1. Control parameters

Oxygen (7782-44-7)			
ACGIH	Not established		
USA OSHA	Not established		

Argon (7440-37-1)		-	
ACGIH	Not established		
USA OSHA	Not established		

#### 8.2. Exposure controls

Appropriate engineering controls

: Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Provide adequate general and local exhaust

ventilation. Consider work permit system e.g. for maintenance activities.

Hand protection

: Wear working gloves when handling gas containers.

Eye protection

Wear safety glasses with side shields.

Respiratory protection

Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.

Thermal hazard protection

: None necessary.

Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

Other information

: Wear safety shoes while handling containers.

SDS ID: P-4718 3/9 10/03/2014 EN (English US)

This document is only controlled while on the Praxair, Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

: No data available

#### Safety Data Sheet

Boiling point

scording to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

## SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Colorless gas.
Color : Colorless
Odor : Odorless.
Odor threshold : No data availai

Odor threshold : No data available pH : Not applicable.
Relative evaporation rate (butyl acetate=1) : No data available Relative evaporation rate (ether=1) : Not applicable.
Melting point : No data available Freezing point : No data available

Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : Not applicable.

Relative vapor density at 20 °C : No data available
Relative density : No data available
Specific gravity / density : 1.65 kg/m³

Solubility : Water: No data available

Log Pow : Not applicable.
Log Kow : Not applicable.
/iscosity, kinematic : Not applicable.
Viscosity, dynamic : Not applicable.
Explosive properties : Not applicable.

Oxidizing properties : None,

Explosive limits : No data available

9.2. Other Information

No additional information available

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

#### 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

No additional information available

#### 10.4. Conditions to avoid

No additional information available

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Using this product in welding and cutting may create additional hazards. The arc from electric arc welding may form gaseous reaction products such as carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc. Other decomposition products of arc welding and cutting originate from the volatilization, reaction, and oxidization of the material being worked.

10/03/2014 EN (English US) SDS ID: P-4718 4/9

Safety Data Sheet

scording to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

#### SECTION IN Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Not classified

pH: Not applicable.

Serious eye damage/irritation : Not classified

pH: Not applicable.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

: Not classified

exposure)

No known effects from this product.

Aspiration hazard : Not classified

Not applicable.

#### SECTION 12. Ecological information

#### 12.1. Toxicity

Ecology - general : No ecological damage caused by this product.

#### 12.2. Persistence and degradability

StarGold O1, O2, O5; M1, M2, M5; Sigma-1, 2,	5	·	<u> </u>	
Persistence and degradability	No ecological damage caused by this			

Oxygen (7782-44-7)	
Persistence and degradability	No ecological damage caused by this product.

Argon (7440-37-1)		$\neg$
Persistence and degradability	No ecological damage caused by this product.	$\neg$

#### 12.3. Bioaccumulative potential

StarGold O1, O2, O5; M1, M2, M5; S	igma-1, 2, 5
BCF fish 1	>=
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

Oxygen (7782-44-7)		
Log Pow	Not applicable.	
Log Kow	Not applicable.	
Bioaccumulative potential	No ecological damage caused by this product.	

Argon (7440-37-1)	
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

#### 12.4. Mobility in soil

StarGold O1, O2, O5; M1, M2, M5; Sigma-1, 2,	5	
Mobility in soil	No data available.	

10/03/2014 EN (English US) SDS ID: P-4718 5/9

Safety Data Sheet

ccording to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Oxygen (7782-44-7)		
Mobility in soil	No data available.	
Ecology - soil	No ecological damage caused by this product.	<u></u>
Argon (7440-37-1)		
Mobility in soil	No data available.	
Ecology - soil	No ecological damage caused by this product.	

12.5. Other adverse effects

Effect on ozone layer

: None.

Effect on the global warming

: No known ecological damage caused by this product.

#### SECTION EXPOSIONS CORRECTIONS

13,1. Waste treatment methods

Waste treatment methods

: May be vented to atmosphere in a well ventilated place. Consult supplier for specific

recommendations. Do not discharge into any place where its accumulation could be dangerous.

Contact supplier if guidance is required.

Waste disposal recommendations

: Dispose of contents/container in accordance with local/regional/national/international regulations.

Contact supplier for any special requirements.

## SECTION (ASTransportantomation)

In accordance with DOT

Transport document description

: UN1956 Compressed gas, n.o.s. (Argon; Oxygen), 2.2

UN-No.(DOT)

: UN1956

Proper Shipping Name (DOT)

: Compressed gas, n.o.s.

(Argon; Oxygen)

Department of Transportation (DOT) Hazard

Classes Hazard labels (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

: 2.2 - Non-flammable gas



**DOT Symbols** 

: G - Identifies proper shipping name (PSN) requiring the addition of technical name(s) in parentheses following the PSN.

Additional information

Other information

: No supplementary information available.

Special transport precautions

: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: -Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is

correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by sea

UN-No. (IMDG)

: 1956

Proper Shipping Name (IMDG)

: COMPRESSED GAS, N.O.S.

Class (IMDG)

: 2 - Gases

Air transport

UN-No.(IATA)

: 1956

Proper Shipping Name (IATA)

: COMPRESSED GAS, N.O.S.

Class (IATA)

10/03/2014

EN (English US)

SDS ID: P-4718

6/9

Safety Data Sheet

eccording to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

## SECTION 15: Regulatory information

15.1. US Federal regulations

StarGold O1, O2, O5; M1, M2, M5; Sigma-1, 2, 5

SARA Section 311/312 Hazard Classes

Sudden release of pressure hazard

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

## 15.2. International regulations

#### CANADA

pressed Gas zing Material

#### Argon (7440-37-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Class A - Compressed Gas

#### **EU-Regulations**

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Ox. Gas 1

H270

Compressed gas H280

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

#### 15.2.2. National regulations

No additional information available

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

#### Oxygen (7782-44-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

### Argon (7440-37-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

## SECTION 16: Other information

Revision date

: 10/3/2014 12:00:00 AM

10/03/2014 EN (English US) SDS ID: P-4718 7/9

Safety Data Sheet

cording to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Fumes and gases produced during welding and cutting processes can be dangerous to your health and may cause serious lung disease. KEEP YOUR HEAD OUT OF FUMES. DO NOT BREATHE FUMES AND GASES. Use enough ventilation, local exhaust, or both to keep fumes and gases from your breathing zone and the general area. Short-term overexposure to fumes may cause dizziness, nausea, and dryness or irritation of the nose, throat, and eyes; or may cause other similar discomfort. Contaminants in the air may add to the hazard of fumes and gases. One such contaminant, chlorinated hydrocarbon vapors from cleaning and degreasing activities, poses a special risk. DO NOT USE ELECTRIC ARCS IN THE PRESENCE OF CHLORINATED HYDROCARBON VAPORS—HIGHLY TOXIC PHOSGENE MAY BE PRODUCED. Metal coatings such as paint, plating, or galvanizing may generate harmful fumes when heated. Residues from cleaning materials may also be harmful. AVOID ARC OPERATIONS ON PARTS WITH PHOSPHATE RESIDUES (ANTI-RUST, CLEANING PREPARATIONS)—HIGHLY TOXIC PHOSPHINE MAY BE PRODUCED.

Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair SDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.com. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (Phone: 1-800-PRAXAIR/1-800-772-9247; Address: Praxair Call Center, Praxair, Inc., P.O. Box 44, Tonawanda, NY 14151-0044).

PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

Full text of H-phrases: see section 16:

The state of the s	
Compressed gas	Gases under pressure Compressed gas
Ox. Gas 1	Oxidizing gases Category 1
H270	MAY CAUSE OR INTENSIFY FIRE; OXIDIZER
H280	CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

NFPA health hazard

: 0 - Exposure under fire conditions would offer no hazard

beyond that of ordinary combustible materials.

NFPA fire hazard

0 - Materials that will not burn.


NFPA reactivity

0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

NFPA specific hazard

: SA - This denotes gases which are simple asphyxiants.



HMIS III Rating

Health

: 0 Minimal Hazard - No significant risk to health

Flammability Physical : 0 Minimal Hazard : 3 Serious Hazard

SDS US (GHS HazCom 2012) - Praxair

10/03/2014

EN (English US)

SDS ID: P-4718

8/9

This document is only controlled while on the Praxair, Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

	Safety	Data	She	et
--	--------	------	-----	----

ocording to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

10/03/2014 EN (English US) SDS ID: P-4718 9/9

	·	