

# Safety Data Sheet

according to OSHA Hazard Communication  
29 CFR Part 1910.1200



## SECTION 1. Identification

**Product Code** 10061

**Product Name:** Xylene

**Supplied by:** EMCO Chemical Distributors, Inc.  
8601 95th Street  
Pleasant Prairie, Wisconsin 53158  
(262) 427-0400  
E-Mail: [information@emcochem.com](mailto:information@emcochem.com)

**24 hr. Emergency:**  
**CHEMTREC:** 1-800-424-9300  
**International:** +1-703-527-3887

NOTE: CHEMTREC emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

## SECTION 2. Hazard(s) Identification

\*\*\* **EMERGENCY OVERVIEW \*\*\*:** Suspect cancer hazard. Flammable liquid and vapor. May be fatal if swallowed and enters airway.

### GHS Classification

Acute Tox. 4 Inhalation, Asp. Tox. 1, Carc. 2, Eye Irrit. 2, Flam. Liq. 3, Skin Irrit. 2, STOT RE 2, STOT SE 3 RTI

### Symbol(s) of Product



**Signal Word**  
Danger

### GHS HAZARD STATEMENTS

|                                        |      |                                                                    |
|----------------------------------------|------|--------------------------------------------------------------------|
| Acute Toxicity, Inhalation, category 4 | H332 | Harmful if inhaled.                                                |
| Aspiration Hazard, category 1          | H304 | May be fatal if swallowed and enters airways.                      |
| Carcinogenicity, category 2            | H351 | Suspected of causing cancer.                                       |
| Eye Irritation, category 2             | H319 | Causes serious eye irritation.                                     |
| Flammable Liquid, category 3           | H226 | Flammable liquid and vapor.                                        |
| STOT, repeated exposure, category 2    | H373 | May cause damage to organs through prolonged or repeated exposure. |
| STOT, single exposure, category 3, RTI | H335 | May cause respiratory irritation.                                  |
| Skin Irritation, category 2            | H315 | Causes skin irritation.                                            |

### GHS PRECAUTIONARY STATEMENTS

|      |                                                                                                |
|------|------------------------------------------------------------------------------------------------|
| P201 | Obtain special instructions before use.                                                        |
| P202 | Do not handle until all safety precautions have been read and understood.                      |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P240 | Ground/bond container and receiving equipment.                                                 |
| P241 | Use explosion-proof electrical/ventilating/lighting/equipment.                                 |
| P242 | Use only non-sparking tools.                                                                   |
| P243 | Take precautionary measures against static discharge.                                          |
| P260 | Do not breathe dust/fume/gas/mist/vapors/spray.                                                |
| P264 | Wash thoroughly after handling.                                                                |
| P271 | Use only outdoors or in a well-ventilated area.                                                |