SAFETY DATA SHEET

1. Identification

Product number

755-8

Product identifier

8 OZ ANTI SEIZE LB 12PK

Company information

1ST AYD. CORPORATION 1325 GATEWAY DRIVE

ELGIN, IL 60124 United States

Emergency telephone US

800-255-3924

Version #

06

Recommended use

Not available.

Recommended restrictions

None known.

2. Hazard(s) identification

Physical hazards

Not classified.

Health hazards

Acute toxicity, oral

Category 4

lealtii Hazai us

Catogo

Acute toxicity, inhalation

Category 4

Serious eye damage/eye irritation

Category 2

Germ cell mutagenicity

Category 1B

Carcinogenicity

Category 1A

Environmental hazards

OSHA defined hazards

Not classified. Not classified.

Label elements



Signal word

Danger

Hazard statement

Harmful if swallowed. Causes serious eye irritation. Harmful if inhaled. May cause genetic defects.

May cause cancer.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective

gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Call a poison center/doctor if you feel unwell. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. If eye

irritation persists: Get medical advice/attention, Collect spillage.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Copper		7440-50-8	20 - 40

Product name: 8 OZ ANTI SEIZE LB 12PK

SD\$ U\$

Version #: 06 Issue date: 05-14-2015

1 / 10

Chemical name	Common name and synonyms	CAS number	%
Triethanolamine		102-71-6	20 - 40
Aluminum		7429-90-5	1 - 2.5
Graphite		7782-42-5	1 - 2.5
Crystalline Silica		14808-60-7	0.1 - 1
Diethanolamine		111-42-2	0.1 - 1
Mineral Spirits		8052-41-3	0.1 - 1
Other components below reportable lev	rels		40 - 60

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing,

Most important symptoms/effects, acute and

redness, swelling, and blurred vision.

delayed

Indication of immediate medical attention and special Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

treatment needed General Information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Sultable extinguishing media

Unsultable extinguishing

media

Alcohol resistant foam. Dry powder. Dry sand. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

During fire, gases hazardous to health may be formed.

the chemical Special protective equipment

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighters

Move containers from fire area if you can do so without risk.

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods General fire hazards

No unusual fire or explosion hazards noted.

Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Dike far ahead of spill for later disposal. Following product recovery, flush area with water.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Avoid inhalation of vapors and spray mists. Avoid prolonged exposure. Do not taste or swallow, When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up, Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	s for Air Contaminants (29 CFR 1910.100 Type	Value	Form
Aluminum (CAS 7429-90-5)	PEL	5 mg/m3	Respirable dust.
		15 mg/m3	Total dust.
Copper (CAS 7440-50-8)	PEL.	1 mg/m3	Dust and mist.
	,	0.1 mg/m3	Fume.
Mineral Spirits (CAS	PEL	2900 mg/m3	
8052-41-3)	F L.L	•	
		500 ppm	
US. OSHA Table Z-3 (29 Cl Components	FR 1910.1000) Type	Value	Form
		0.3 mg/m3	Total dust.
Crystalline Silica (CAS 14808-60-7)	TWA	0.5 mg/ms	· Otal dust.
•		0.1 mg/m3	Respirable.
		2,4 mppcf	Respirable.
Graphite (CAS 7782-42-5)	TWA	15 mppcf	,
US. ACGIH Threshold Lim			_
Components	Туре	Value	Form
Aluminum (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
		0.2 mg/m3	Fume.
Crystalline Silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Diethanolamine (CAS 111-42-2)	TWA	1 mg/m3	Inhalable fraction and vapor.
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
Mineral Spirits (CAS 8052-41-3)	TWA	100 ppm	
Triethanolamine (CAS 102-71-6)	TWA	5 mg/m3	
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	Form
Aluminum (CAS 7429-90-5)	TWA	5 mg/m3	Respirable.
•		5 mg/m3	Welding fume or pyrophoric powder.
		10 mg/m3	Total
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
Crystalline Silica (CAS	TWA	0.05 mg/m3	Respirable dust.
14808-60-7)			·
Diethanolamine (CAS 111-42-2)	TWA	15 mg/m3	
-		3 ppm	
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.
Mineral Spirits (CAS	Ceiling	1800 mg/m3	
8U5Z-41-3)			
8052-41-3)	TWA	350 mg/m3	

Exposure guidelines

US - California OELs: Skin designation

Diethanolamine (CAS 111-42-2)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Diethanolamine (CAS 111-42-2)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airporne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Hand protection

Wear appropriate chemical resistant gloves.

Skin protection

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Skin protection

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Not available.

Color

Not available.

Odor

Not available. Not available.

Odor threshold

Not available.

Melting point/freezing point Initial boiling point and boiling Not available. 1822.01 °F (994.45 °C) estimated

range

Flash point

648.9 °F (342.7 °C) estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

0,00001 psig @70F estimated

Vapor density

Not available.

Relative density

Not available,

Solubility(les)

Sclubility (water)

Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-Ignition temperature

Not available.

Decomposition temperature

Not available.

Viscosity

Not available.

#755-8

Other information

Specific gravity 2.845 estimated

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Possibility of hazardous

Material is stable under normal conditions. Hazardous polymerization does not occur.

reactions

Conditions to avoid

Incompatible materials

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Peroxides. Phenols.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion

Harmful if swallowed.

Inhalation

Harmful if inhaled.

Skin contact

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

Eye contact

Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Components

Harmful if inhaled. Harmful if swallowed.

Components	Species	Test Results
Aluminum (CAS 7429-90-5)		
Acute		
Inhalation		
LC50	Rat	> 0.888 mg/l, 4 Hours
		7.6 mg/l, If <1L: Consumer Commodity Hours
Oral		
LD50	Rat	> 15900 mg/kg
Copper (CAS 7440-50-8)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	300 - 500 mg/kg
Diethanolamine (CAS 111-42	2-2)	
Acute		
Oral		•
LD50	Rat	1100 mg/kg
Graphite (CAS 7782-42-5)		
Acute		•
Inhalation		
LC50	Rat	> 2000 mg/m3, 4 Hours
Triethanolamine (CAS 102-7	1-6)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg

Version #: 06 | Issue date: 05-14-2015

#755-8 Components **Species Test Results** Oral LD50 Rat 6400 mg/kg * Estimates for product may be based on additional component data not shown. Prolonged skin contact may cause temporary irritation. Skin corresion/irritation Serious eye damage/eye Causes serious eye irritation. irritation Respiratory or skin sensitization Respiratory sensitization Not available. This product is not expected to cause skin sensitization. Skin sensitization Germ cell mutagenicity May cause genetic defects. Carcinogenicity May cause cancer. IARC Monographs. Overall Evaluation of Carcinogenicity Crystalline Silica (CAS 14808-60-7) If <1L: Consumer Commodity Carcinogenic to humans. Diethanolamine (CAS 111-42-2) 2B Possibly carcinogenic to humans. Triethanolamine (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. Reproductive toxicity This product is not expected to cause reproductive or developmental effects. Specific target organ toxicity -Not classified. single exposure Not classified. Specific target organ toxicity repeated exposure Aspiration hazard Not available. Prolonged inhalation may be harmful. May be harmful if absorbed through skin. Prolonged Chronic effects exposure may cause chronic effects. Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans. 12. Ecological information Very toxic to aquatic life with long lasting effects. **Ecotoxicity**

	,	to advant in a new tong transition	
Components		Species	Test Results
Aluminum (CAS 7429-	90-5)		
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.16 mg/l, 96 hours
Copper (CAS 7440-50-	-8)		
Aquatic			
Algae	1C50	Algae	0 mg/L, 72 Hours
Crustacea	EC50	Daphnia	0.03 mg/L, 48 Hours
		Water flea (Daphnia magna)	0.036 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	0.0319 - 0.0544 mg/l, 96 hours
Diethanolamine (CAS	111-42-2)		
Aquatic			
Algae	IC50	Algae	7.8 mg/L, 72 Hours
Crustacea	EC50	Daphnia	55 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Plmephales promelas)	100 mg/l, 96 hours
Triethanolamine (CAS	102-71-6)		
Aquatic			
Algae	1C50	Algae	216 mg/L, 72 Hours
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	565.2 - 658.3 mg/l, 48 hours

#755-8

Components **Species Test Results** LC50 Fathead minnow (Pimephales promelas) 10610 - 13010 mg/l, 96 hours Fish

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bloaccumulative potential

No data available.

Partition coefficient n-octanol / water (log Kow)

Diethanolamine Mineral Spirits

-1.433.16 - 7.15

Triethanolamine

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations, Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

HN3082 **UN** number

UN proper shipping name

Transport hazard class(es)

Class 9 Subsidiary risk 9

Label(s) Packing group

Ш Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

8, 146, 335, IB3, T4, TP1, TP29 Special provisions 155

Packaging exceptions 203 Packaging non bulk Packaging bulk 241

IATA

UN3082 UN number

UN proper shipping name Environmentally hazardous substances, liquid, n.o.s. (Copper, Aluminum)

Transport hazard class(es)

Class 9 Subsidiary risk 9

Label(s) Packing group Ш Yes Environmental hazards

Other Information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Environmentally hazardous substances, liquid, n.o.s. (Copper, Aluminum)

Passenger and cargo

aircraft

Forbidden.

Cargo aircraft only **Packaging Exceptions**

Forbidden. 155

IMDG

UN number

UN3082

Version #: 06 Issue date: 05-14-2015

UN proper shipping name Transport hazard class(es) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Copper, Aluminum)

Class

Subsidiary risk

9

Label(s)
Packing group

9 III

Environmental hazards

Marine pollutant

Yes

EmS

F-A, S-F

Special precautions for use Transport in bulk according to

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

This substance/mixture is not intended to be transported in bulk.

Annex II of MARPOL 73/78 and the IBC Gode

DOT: IATA; IMDG



Marine pollutant



General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Copper (CAS 7440-50-8)

Listed.

Diethanolamine (CAS 111-42-2)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

Product name: 8 OZ ANTI SEIZE LB 12PK

SDS US

SARA 311/312 Hazardous

chemical

#755-8

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Соррег	7440-50-8	20 - 40	
Aluminum	7429-90-5	1 - 2.5	
Diethanolamine	111 -42- 2	0.1 - 1	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Diethanolamine (CAS 111-42-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Aluminum (CAS 7429-90-5)

Copper (CAS 7440-50-8)

Crystalline Silica (CAS 14808-60-7)

Diethanolamine (CAS 111-42-2)

Graphite (CAS 7782-42-5)

Mineral Spirits (CAS 8052-41-3)

Triethanolamine (CAS 102-71-6)

US. New Jersey Worker and Community Right-to-Know Act

Aluminum (CAS 7429-90-5)

Copper (CAS 7440-50-8)

Crystalline Silica (CAS 14808-60-7)

Diethanolamine (CAS 111-42-2)

Graphite (CAS 7782-42-5)

Mineral Spirits (CAS 8052-41-3)

Triethanolamine (CAS 102-71-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminum (CAS 7429-90-5)

Copper (CAS 7440-50-8)

Crystalline Silica (CAS 14808-60-7)

Diethanolamine (CAS 111-42-2)

Graphite (CAS 7782-42-5)

Mineral Spirits (CAS 8052-41-3)

Triethanolamine (CAS 102-71-6)

US. Rhode Island RTK

Aluminum (CAS 7429-90-5)

Copper (CAS 7440-50-8)

Diethanolamine (CAS 111-42-2)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer,

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Diethanolamine (CAS 111-42-2)

Listed: June 22, 2012

International Inventories

Country(s) or region	Inventory name	On Inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan _.	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
Product name: 8 OZ ANTI SEIZE	LB 12PK	CDO LIG

Product name: 8 OZ ANTI SEIZE LB 12PK

ads us

Version #: 06 Issue date: 05-14-2015

9/10

#755-8

Country(s) or region

Inventory name

On inventory (yes/no)*

New Zealand

New Zealand Inventory

Philippines

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

No

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

Issue date

05-14-2015

Version #

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.