SAFETY DATA SHEET

#40A

1. Identification

Product number

1000005341

Product identifier

1ST AYD GLASS CLEANER #40-A

Company information

1ST AYD. CORPORATION 1325 GATEWAY DRIVE ELGIN, IL 60124 United States

Emergency telephone US

800-255-3924

Recommended use

cleaner

Recommended restrictions

None known.

2. Hazard(s) identification

Physical hazards

Gases under pressure

Liquefied gas

Health hazards

Not classified.

Environmental hazards

Not classified.

OSHA defined hazards

Not classified.

Label elements



Signal word

Warning

Hazard statement

Contains gas under pressure; may explode if heated.

Precautionary statement

Prevention

Observe good industrial hygiene practices.

Response

Wash hands after handling.

Storage

Protect from sunlight. Store in a well-ventilated place.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|----------|
| 2-Butoxyethanol | | 111-76-2 | 2.5 - 10 |
| Ethyl Alcohol | | 64-17-5 | 2.5 - 10 |
| Butane | | 106-97-8 | 1 - 2.5 |
| Propane | | 74-98-6 | 1 - 2.5 |
| Other components below reportable levels | | | 90 - 100 |

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Move to fresh air. Get medical attention if symptoms persist.

Skin contact

Get medical attention if irritation develops and persists.

Eye contact

Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

General information

Direct contact with eyes may cause temporary irritation.

Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. See Section 8 of the SDS for Personal Protective Equipment. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the

8. Exposure controls/personal protection

| Occupational exposure li | umits |
|--------------------------|-------|
|--------------------------|-------|

| US. OSHA Table Z-1 Limits for Air Components | Туре | Value | |
|--|--------------|------------|--|
| 2-Butoxyethanol (CAS 111-76-2) | PEI. | 240 mg/m3 | |
| | | 50 ppm | |
| Ethyl Alcohol (CAS 64-17-5) | PEL | 1900 mg/m3 | |
| | | 1000 ppm | |
| Propane (CAS 74-98-6) | PEL | 1800 mg/m3 | |
| | | 1000 ppm | |
| US. ACGIH Threshold Limit Values | | | |
| Components | Туре | Value | |
| 2-Butoxyethanol (CAS 111-76-2) | TWA | 20 ppm | |
| Butane (CAS 106-97-8) | STEL | 1000 ppm | |
| Ethyl Alcohol (CAS 64-17-5) | STEL | mqq 0001 | |
| US. NIOSH: Pocket Guide to Chemi | ical Hazards | •• | |
| Components | Туре | Value | |
| 2-Butoxyethanol (CAS 111-76-2) | TWA | 24 mg/m3 | |
| | | 5 ppm | |
| 3utane (CAS 106-97-8) | TWA | 1900 mg/m3 | |

Biological limit values

Ethyl Alcohol (CAS 64-17-5)

Propane (CAS 74-98-6)

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------------------|----------|--|---------------------|---------------|
| 2-Butoxyethanol (CAS 111-76-2) | 200 mg/g | Butoxyacetic acid (BAA), with hydrolysis | Creatinine in urine | * |

TWA

TWA

Exposure guidelines

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

1900 mg/m3 800 ppm

1900 mg/m3 1000 ppm

1800 mg/m3 1000 ppm

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2)

Skin designation applies.

US - Tennesse OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

If contact is likely, safety glasses with side shields are recommended.

Hand protection

For prolonged or repeated skin contact use suitable protective gloves.

Skin protection

Other

Wear suitable protective clothing.

^{* -} For sampling details, please see the source document.

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smake. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Clear. Gas.

Physical state

Aerosol. Liquefied gas.

Form Color

Light yellow.

Odor

Characteristic.

Odor threshold

Not available.

рΗ

9.1 - 10.1 estimated

Melting point/freezing point

Not available.

Initial boiling point and boiling

212 °F (100 °C) estimated

range

-156.0 °F (-104.4 °C) Propellant estimated

Flash point

Not available.

Evaporation rate Flammability (solid, gas)

Upper/lower flammability or explosive limits

Not available.

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

(%)

Not available.

Explosive limit - lower (%) Explosive limit - upper (%)

Not available.

Vapor pressure

80 - 100 psig @70F estimated

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature

Not available.

Decomposition temperature

Not available.

Viscosity

Not available.

Other Information

Aerosol spray enclosed space

Deflagration density

> 2.52 g/cm3 Tested

Aerosol spray ignition

Specific gravity

< 15 cm Tested estimated

distance

0.977 - 0.997

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials

Hazardous decomposition

Strong oxidizing agents.

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion

Expected to be a low ingestion hazard.

Inhalation

Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Eye contact

Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

May be harmful if swallowed. May be harmful in contact with skin. May be harmful if inhaled. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Components Species Test Results 2-Butoxyethanol (CAS 111-76-2) Acute Dermal LD50 Guinea pig 230 ml/kg, 24 Hours 7.3 ml/kg, 4 Days Rabbit 450 mi/kg, 24 Hours 435 mg/kg, 24 Hours 0.63 ml/kg Rat > 2000 mg/kg, 24 Hours Inhalation LC50 Rabbit 400 ppm, 7 Hours Rat 450 ppm, 4 Hours Oral LD100 Rabbit 695 mg/kg LD50 Dog > 695 mg/kg Guinea pig 1200 mg/kg Rat 530 - 2800 mg/kg Butane (CAS 106-97-8) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l Ethyl Alcohol (CAS 64-17-5) Acute Inhalation LC50 Cat 85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours Mouse > 60000 ppm 79.43 mg/l, 134 Minutes Rat

> 115.9 mg/l, 4 Hours

| | | #40A | |
|--|--|---|--|
| Components | Species | Test Results | |
| | | 51.3 mg/l, 6 Hours | |
| Oral | | | |
| LD50 | Monkey | 6000 mg/kg | |
| | Mouse | 10500 ml/kg | |
| | Rat | 1187 - 2769 mg/kg | |
| | | 7800 ml/kg | |
| Propane (CAS 74-98-6) | | • | |
| Acute | | | |
| Inhalation | | | |
| LC50 | Mouse | 1237 mg/l, 120 Minutes | |
| | | 52 %, 120 Minutes | |
| | Rat | 1355 mg/l | |
| | | 658 mg/l/4h | |
| * Estimates for anadust moul | ha tanan di 196 di 197 | | |
| Skin corrosion/irritation | be based on additional component data not | | |
| Serious eye damage/eye | May be irritating to the skin. Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation. May be irritating to eyes. | | |
| rritation | blied contact with eyes may cause temp | porary irritation. May be irritating to eyes. | |
| Respiratory or skin sensitizatio | n | | |
| Respiratory sensitization | Not a respiratory sensitizer. | | |
| Skin sensitization | This product is not expected to cause skin sensitization. | | |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | | |
| Carcinogenicity | This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. | | |
| IARC Monographs. Overali | Evaluation of Carcinogenicity | | |
| | 11-76-2) 3 Not clas ed Substances (29 CFR 1910.1001-1050) | ssifiable as to carcinogenicity to humans. | |
| Not listed. | | | |
| eproductive toxicity | This product is not expected to cause rep | roductive or developmental effects. | |
| pecific target organ toxicity - Ingle exposure | Not classified. | | |
| pecific target organ toxicity - peated exposure | Not classified. | | |
| spiration hazard | Not an aspiration hazard. Not likely, due to | o the form of the product. | |
| hronic effects | Prolonged inhalation may be harmful. May be harmful if absorbed through skin. | | |
| | 2-Butoxy ethanol may be absorbed throug prolonged. These effects have not been of | th the skin in toxic amounts if contact is repeated and observed in humans. | |
| 2. Ecological information | | | |
| otoxicity | Harmful to aquatic life. | | |
| Product | Species | | |

| otoxicity | Harmful t | o aquatic life. | | |
|----------------------|----------------|---------------------------------------|-------------------------------------|--|
| Product | Species | | Test Results | |
| 19 OZ 1ST AYD GLAS | S CLEANER LB 2 | 4PK (CAS Mixture) | | |
| Aquatic | | , | | |
| Crustacea | EC50 | Daphnia | 13838.1602 mg/l, 48 hours estimated | |
| Components | | Species | Test Results | |
| 2-Butoxyethanol (CAS | 111-76-2) | | | |
| Aquatic | | | | |
| Fish | LC50 | Inland silverside (Menidia beryllina) | 1250 mg/l, 96 hours | |

| | | | #40A |
|---|--|---|---|
| Components | · | Species | Test Results |
| Ethyl Alcohol (CAS 64-17-5) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 7700 - 11200 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | <u> </u> |
| * Estimates for product may I | be based on | additional component data not shown. | |
| Persistence and degradability | | available on the degradability of this product. | |
| Bioaccumulative potential | No data a | | |
| Partition coefficient n-octai | nol / water (i | log Kow) | |
| 2-Butoxyethanol | • | 0.83 | |
| Butane | | 2.89 | |
| Ethyl Alcohol | | -0.31 | |
| Propane | 2.36 | | |
| Mobility In soil | No data a | | |
| Other adverse effects | No other a potential, o | ndverse environmental effects (e.g. ozone deple endocrine disruption, global warming potential) | etion, photochemical ozone creation are expected from this component. |
| 13. Disposal consideration | ns | | |
| Disposal instructions | Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations. | | |
| Local disposal regulations | Dispose in accordance with all applicable regulations. | | |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. | | |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). | | |
| Contaminated packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers. | | |
| 14. Transport information | | | |
| DOT | | | |
| UN number | UN1950 | | |
| UN proper shipping name | Aerosols | | |
| Transport hazard class(es) | | | |
| Class | 2.2 | | |
| Subsidiary risk | - | | |
| Label(s) | 2.2 | | |
| Packing group | Not applica | | |
| | | y instructions, SDS and emergency procedures | before handling. |
| Packaging exceptions Packaging non bulk | 306 None | | |
| Packaging bulk | None None | | |
| This product meets the excepti Until 12/31/2020, the "Consum mark for packages of UN 1950 | ion requirem er Commodi Aerosols, Li | ents of section 173.306 as a limited quantity an ty - ORM-D' marking may still be used in place mited quantities require the limited quantity dia sumer Commodity ORM-D" marking and both rr | of the new limited quantity diamond |
| ATA | | making and buttir | ау ве изріауви сопситенцу. |
| UN number | UN1950 | | |
| UN proper shipping name | | on-flammable | |
| Transport hazard class(es) | | | |
| Class | 2,2 | | |
| Subsidiary risk | - | | |
| Label(s) | 2.2 | | |

Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

No.

2L

Packing group Environmental hazards

ERG Code

Other information

Passenger and cargo

Alfowed.

aircraft

Cargo aircraft only **Packaging Exceptions**

Allowed, LTD QTY

IMDG

UN number

UN1950

UN proper shipping name

AEROSOLS

Transport hazard class(es)

Class

2.2

Subsidiary risk

Label(s)

2.2

Packing group

Not applicable.

Environmental hazards

Marine pollutant

Nο.

EmS

Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions

LTD QTY

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List,

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TR! reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2) Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2) Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2) Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventorles

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | Na Na |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | . No |
| New Zealand | New Zealand Inventory | No. |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |

#40A

Country(s) or region

Inventory name

On inventory (yes/no)*

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

V---

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date

05-14-2015

Version #

01

References

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision Information

Product and Company Identification: Alternate Trade Names