



Item 744

Issuing Date 07-May-2017

Revision Date 07-May-2018

SAFETY DATA SHEET

Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND OF THE COMPANY UNDERTAKING

Product Identifier

Product Name

Complete Fuel Treatment

Other means of identification

Synonyms

None

Recommended use of the chemical and restrictions on use

Recommended Use

Fuel additive

Uses advised against

No information available

Details of the supplier of the safety data sheet

Supplier Name

Enertech Labs, Inc.

Supplier Address

PO Box 732
Gatzville NY

14068

US

Supplier Phone Number

Phone: 800-759-2080
Fax: 716-328-1786
Contact Phone: 716-597-5761

Supplier Email

sales@enertechlabs.com

Emergency telephone number

Chemtrec 800-424-9300

2. HAZARD IDENTIFICATION


Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Chemical mutagenicity	Category 1B
Carcinogenicity	Category 1B

Aspiration Toxicity	Category 1
Flammable liquids	Category 4

GHS Label elements, including precautionary statements

Signal word	Danger	Emergency Overview
<p>Hazard Statements</p> <p>Harmful if swallowed</p> <p>Harmful if inhaled</p> <p>Causes skin irritation</p> <p>Causes serious eye irritation</p> <p>May cause genetic defects</p> <p>May cause cancer</p> <p>May be fatal if swallowed and enters airways</p> <p>Combustible liquid</p>		
		
Appearance Amber	Physical state Liquid	Other Sweet

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Avoid breathing dust/fume/gas/mist/vapour/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Wear eye/face protection

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental list and instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Ingestion

Rinse mouth
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

2.62% of the mixture consists of ingredient(s) of unknown toxicity

Other Information

May be harmful in contact with skin
 Toxic to aquatic life with long lasting effects
 PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION
 INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
butyl cellosolve	111-76-2	10 - 30	*
Xylene	1330-20-7	10 - 30	*
Naphtha (petroleum), heavy aromatic	64742-94-5	10 - 30	*
Petroleum naphtha, light aromatic	64742-95-8	7 - 13	*
1,2,4-Trimethylbenzene	95-63-6	7 - 13	*
2-Ethylhexyl nitrate	27247-96-7	7 - 13	*
Ethylbenzene	100-41-4	1 - 5	*
Naphthalene	91-20-3	1 - 5	*
1,3,5-Trimethylbenzene	108-67-8	1 - 5	*
2-ethylhexan-1-ol	104-76-7	1 - 5	*
Cumene	98-92-8	1 - 5	*
Diethyl Benzene	25340-17-4	1 - 5	*
Vinyl acetate	108-05-4	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures**General Advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

Skin contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation, if breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Dizziness.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, Carbon dioxide (CO₂), Water spray, Alcohol resistant foam.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.

Uniform Fire Code

Inflant; Liquid
Toxic; Liquid
Combustible Liquid; III-A

Hazardous Combustion Products

Carbon oxides, Carbon monoxide, Carbon dioxide (CO₂).

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge

Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Avoid breathing vapors or mists. Avoid generation of dust. Evacuate personnel to safe areas. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled material. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

HANDLING AND STORAGE**Precautions for safe handling****Handling**

Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up. Protect from moisture. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products

Strong acids. Strong oxidizing agents. Strong bases. Acid chlorides. Acid anhydrides. Chloroformates. Strong reducing agents.

8. EXPOSURE/CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
butyl cellosolve 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) ST	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	
1,2,4 Trimethylbenzene 82-65-8	-	-	TWA: 25 ppm TWA: 125 mg/m ³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 mg/m ³ STEL: 545 mg/m ³
Naphthalene 91-20-3	TWA: 10 ppm S [*]	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
1,3,5-Triethylbenzene 108-67-8	-	-	TWA: 25 ppm TWA: 125 mg/m ³
2-ethylhexan-1-ol 104-76-7	-	-	TWA: 50 ppm TWA: 270 mg/m ³
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³

Vinyl acetate 106-05-4	STEL: 15 ppm TWA: 10 ppm	(vacated) S*	Ceiling: 4 ppm 15 min Ceiling: 15 mg/m ³ 15 min
		(vacated) TWA: 10 ppm (vacated) TWA: 30 mg/m ³ (vacated) STEL: 20 ppm (vacated) STEL: 60 mg/m ³	

ACGIH TLV, American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 985 F.2d 962 (11th Cir., 1992) See section 15 for rational exposure control parameters

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

None required for consumer use. If splashes are likely to occur.: Tight sealing safety goggles.

Skin and body protection

Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.

Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Liquid	Odor	Sweet
Appearance	Amber	Odor Threshold	No information available
Color	No information available		

PROPERTY	VALUES	Remarks Method
pH	UNKNOWN	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	113 °C / 235 °F	None known
Flash Point	63 °C / 145 °F	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	None known
Lower flammability limit	No data available	None known
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Slightly soluble	None known
Solubility in other solvents	No data available	None known

Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	4.8	None known
Explosive properties	No data available	None known
Oxidizing properties	No data available	
Other information		
Softening Point	No data available	
VOC Content (%)	No data available	
Particle Size	No data available	
Particle Size Distribution	No data available	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat. Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases. Acid chlorides. Acid anhydrides. Chloroformates. Strong reducing agents.

Hazardous Decomposition Products

Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product information

Inhalation

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components). Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.

Eye contact

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation. May cause irritation.

Skin contact

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation. Repeated exposure may cause skin dryness or cracking.

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Harmful if swallowed. (based on components). Potential for

aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonia. May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
butyl cellosolve 111-76-2	= 470 mg/kg (Rat)	= 220 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 47635 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Naphthalene (petroleum), heavy 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
Petroleum naphthalene, light aromatic 64742-95-8	-	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h = 3400 ppm (Rat) 4 h = 18 g/m ³ (Rat) 4 h
1,2,4 Trimethylbenzene 95-83-8	= 3400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
2-Ethylhexyl nitrate 27247-96-7	> 2000 mg/kg (Rat)	> 4820 mg/kg (Rabbit)	> 4.6 mg/L (Rat) 1 h = 14 mg/L (Rat) 4 h = 17.2 mg/L (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Naphthalene 91-20-3	-	> 20 g/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h
1,3,5-Trimethylbenzene 106-67-8	-	-	= 24 g/m ³ (Rat) 4 h
2-ethylhexan-1-ol 104-76-7	1516 - 2774 mg/kg (Rat)	> 1800 mg/kg (Rat)	= 0.237 mg/L (Rat) 4 h
Oleic acid 112-80-1	> 5000 mg/kg (Rat)	-	-
Cumene 98-92-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	-
Vinyl acetate 106-68-4	= 2920 mg/kg (Rat)	= 2220 mg/kg (Rabbit)	= 11400 mg/m ³ (Rat) 4 h = 11.4 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms

Erythema (skin redness). May cause redness and tearing of the eyes. Coughing and/or wheezing. Difficulty in breathing. Asthma-like and/or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Mutagenic Effects

Contains a known or suspected mutagen.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
butyl cellosolve 111-76-2	A3	Group 3		
Xylene 1330-20-7		Group 3		
2-Ethylhexyl nitrate 27247-96-7		Group 2A		X
Ethylbenzene 100-41-4	A3	Group 2B		X
Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	X

Cumene		Group 2B		X
98-82-8				
Vinyl acetate	A3	Group 2B		X
108-05-4				

ACGIH (American Conference of Governmental Industrial Hygienists)**A3 - Animal Carcinogen****IARC (International Agency for Research on Cancer)****Group 2A - Probably Carcinogenic to Humans****Group 2B - Possibly Carcinogenic to Humans****Group 3 - Not Classifiable as to Carcinogenicity in Humans****NTP (National Toxicology Program)****Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen****OSHA (Occupational Safety and Health Administration of the US Department of Labor)****X - Present****Reproductive toxicity**

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

No information available.

Chronic Toxicity

Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Aspiration may cause pulmonary edema and pneumonitis. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.

Target Organ Effects

Respiratory system, Eyes, Skin. May affect the genetic material in germ cells (sperm and eggs). Gastrointestinal tract (GI), Blood, Central Nervous System (CNS), Hematopoietic system, Kidney, Liver, Lungs, Nasal cavities, Thyroid, Central Vascular System (CVS), Testes.

Aspiration Hazard

No information available.

Numerical measures of toxicity: Product information.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
1,286.00 mg/kg
ATEmix (dermal)
2,414.00 mg/kg (ATE)
ATEmix (inhalation-gas)
12,784.00 ppm (4 hr)
ATEmix (inhalation-dust/mist)
2.00 mg/l
ATEmix (inhalation-vapor)
28.00 ATEmix

13 DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal methods**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number

U055 U165 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene 100-41-4		Included in waste stream: F039		
Naphthalene 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145		U165
Cumene 98-82-6				U055

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Naphthalene 91-20-3			Toxic waste Waste number: F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Xylene 1330-20-7	Toxic Ignitable
1,2,4 Trimethylbenzene 98-63-8	Toxic
Ethylbenzene 100-41-4	Toxic Ignitable
Naphthalene 91-20-3	Toxic
Cumene 98-82-8	Toxic Ignitable
Vinyl acetate 108-05-4	Toxic Ignitable

14. TRANSPORT INFORMATION**DOT**

Proper Shipping Name
Hazard Class
Marine Pollutant

NOT REGULATED
NON REGULATED
N/A

This product contains a chemical which is listed as a marine pollutant according to DOT

TDG

Marine Pollutant

Not regulated
This product contains a chemical which is listed as a marine pollutant according to TDG.

MEX

Not regulated

ICAO

Not regulated

IATA

Proper Shipping Name
Hazard Class

Not regulated
NON REGULATED
N/A

IMDG/IMO

Hazard Class
Marine Pollutant

Not regulated
N/A
Product is a marine pollutant according to the criteria set by IMDG/IMO

RID

Not regulated

ADR

Not regulated

ADN

Not regulated

International Inventories**16. REGULATORY INFORMATION****TSCA**

Complies

DSL

All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Name	CAS No	Weight %	SARA 313 - Threshold Values %
BUTYL cellosolve - 111-76-2	111-76-2	10 - 30	1.0
Xylene - 1330-20-7	1330-20-7	10 - 30	1.0
1,2,4 Trimethylbenzene - 95-63-6	95-63-6	7 - 13	1.0
Ethylbenzene - 100-41-4	100-41-4	1 - 5	0.1
Naphthalene - 91-20-3	91-20-3	1 - 5	0.1
Cumene - 98-82-8	98-82-8	1 - 5	1.0
Vinyl acetate - 108-05-4	108-05-4	0.1 - 1	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard

Yes

Chronic Health Hazard
Fire Hazard
Sudden release of pressure hazard
Reactive Hazard

Yes
Yes
No
No

CWA (Clean Water Act)
This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb			X
Ethylbenzene 100-41-4	1000 lb	X	X	X
Naphthalene 91-20-3	100 lb	X	X	X
Vinyl acetate 108-05-4	5000 lb			X

CERCLA
This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Xylene 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Naphthalene 91-20-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Cumene 98-82-8	5000 lb		RQ 0.454 kg final RQ RQ 5000 lb final RQ
Vinyl acetate 108-05-4	5000 lb	5000 lb	RQ 2270 kg final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen
Naphthalene - 91-20-3	Carcinogen
Cumene - 98-82-8	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
butyl cellosolve 111-76-2	X	X	X	X	X
Xylene 1330-20-7	X	X	X	X	X
1,2,4 Trimethylbenzene 95-63-6	X	X	X	X	X
Ethylbenzene 100-41-4	X	X	X	X	X
Naphthalene 91-20-3	X	X	X	X	X
1,3,5-Trimethylbenzene	X	X	X		X

108-67-8					
2-ethylhexan-1-ol	X	X	X		
104-76-7					
Cumene	X	X	X	X	X
98-82-8					
Diethyl Benzene	X				
25340-17-4					
Vinyl acetate	X	X	X	X	X
108-05-4					

International Regulations**Mexico****National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Bulky Cellulose 111-76-2 (10 - 30)		Mexico: TWA 25 ppm Mexico: TWA 120 mg/m ³ Mexico: STEL 75 ppm Mexico: STEL 380 mg/m ³
Xylene 1330-20-7 (10 - 30)		Mexico: TWA 100 ppm Mexico: TWA 435 mg/m ³ Mexico: STEL 150 ppm Mexico: STEL 655 mg/m ³
1,2,4 Trimethylbenzene 85-83-6 (7 - 13)		Mexico: TWA 25 ppm Mexico: TWA 125 mg/m ³ Mexico: STEL 35 ppm Mexico: STEL 170 mg/m ³
Ethylbenzene 100-41-4 (1 - 5)		Mexico: TWA 100 ppm Mexico: TWA 435 mg/m ³ Mexico: STEL 125 ppm Mexico: STEL 545 mg/m ³
Naphthalene 91-20-3 (1 - 5)		Mexico: TWA 10 ppm Mexico: TWA 50 mg/m ³ Mexico: STEL 15 ppm Mexico: STEL 75 mg/m ³
1,3,5-Trimethylbenzene 108-67-8 (1 - 5)		Mexico: TWA 25 ppm Mexico: TWA 125 mg/m ³ Mexico: STEL 35 ppm Mexico: STEL 170 mg/m ³
Cumene 98-82-8 (1 - 5)		Mexico: TWA 50 ppm Mexico: TWA 245 mg/m ³ Mexico: STEL 75 ppm Mexico: STEL 385 mg/m ³
Vinyl acetate 108-05-4 (0.1 - 1)	A3	Mexico: TWA 10 ppm Mexico: TWA 30 mg/m ³ Mexico: STEL 20 ppm Mexico: STEL 80 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens
A3 - Confirmed Animal Carcinogen

Canada**WHMIS Hazard Class**

B3 - Combustible liquid

D2A - Very toxic materials

D2B - Toxic materials





6. OTHER INFORMATION

NFPA	Health Hazards 3	Flammability 2	Instability 0	Physical and Chemical Hazards - Personal Protection
HMIS	Health Hazards 2 *	Flammability 2	Physical Hazard 0	X

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By

Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-8501
07-May-2015
Revision Note
No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet