



Item 743

SAFETY DATA SHEET

Revision Number 1

Issuing Date 06-May-2015

Revision Date 06-May-2018

1. IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND OF THE COMPANY UNDERTAKING

Product Identifier

Product Name Inject R Clean

Other means of Identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Fuel additive

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Evertech Labs, Inc.
Supplier Address 714 Northland Ave
Buffalo
NY
14211
US

Supplier Phone Number Phone: 716-697-5761
Fax: 716-697-0217
Contact Phone 716-697-5761

Supplier Email rgreene@evertechlabs.com

Emergency telephone number Chemtrec 800-424-9300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1

Fammable liquids	Category 4
------------------	------------

GHS Label elements, including precautionary statements

Emergency Overview			
Signal word	Danger	Physical state	Odor
	Hazard Statements Harmful if inhaled Causes skin irritation Causes serious eye irritation May cause genetic defects May cause cancer May cause respiratory irritation May be fatal if swallowed and enters airways Combustible liquid	Liquid	Sweet
			
Appearance	Amber	Physical state	Odor
Precautionary Statements - Prevention Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Wash face, hands and any exposed skin thoroughly after handling Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep cool Wear eye/face protection			
Precautionary Statements - Response IF exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label)			
Eyes IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing if eye irritation persists. Get medical advice/attention			
Skin IF ON SKIN: Wash with plenty of soap and water IF skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse			
Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing			

Ingestion
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Fire
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage
Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity
0% of the mixture consists of ingredient(s) of unknown toxicity

Other Information

Toxic to aquatic life with long lasting effects
Harmful to aquatic life
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals
Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Petroleum naphtha, light aromatic	64742-95-6	15 - 40	*
1,2,4 Trimethylbenzene	95-69-6	15 - 40	*
Naphtha (petroleum), heavy aromatic	64742-94-5	3 - 7	*
Xylene	1330-20-7	1 - 5	*
1,3,5-Trimethylbenzene	106-67-8	1 - 5	*
Cumene	98-82-8	1 - 5	*
Diethyl Benzene	25340-17-4	1 - 5	*
2-Ethylhexyl nitrate	27247-96-7	1 - 5	*
Naphthalene	91-20-3	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice
Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

Skin contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed**Most Important Symptoms and Effects**

Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Dizziness.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, Carbon dioxide (CO2), Water spray, Alcohol resistant foam.

Unsuitable extinguishing media
CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical
Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.

Uniform Fire Code
Inflant Liquid
Toxic Liquid
Combustible Liquid: III-A

Hazardous Combustion Products
Carbon oxides.

Explosion Data
Sensitivity to Mechanical Impact No.
Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions
Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Avoid breathing vapors or mists. Avoid generation of dust. Evacuate personnel to safe areas. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material.

Other Information
Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions
Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment
Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled material. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up
Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE**Precautions for safe handling****Handling**

Do not breathe dust/fume/gas/mist/vapour/spray.

Conditions for safe storage, including any incompatibilities**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up. Protect from moisture. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products

Strong acids. Strong oxidizing agents. Strong bases.

8: EXPOSURE CONTROL/PERSONAL PROTECTION**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
1,2,4 Trimethylbenzene 95-53-6	-	-	TLV: 25 ppm TWA: 125 mg/m ³
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	
1,3,5-Triethylbenzene 100-67-8	-	-	TWA: 25 ppm TWA: 125 mg/m ³
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S ⁻	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³
Naphthalene 91-20-3	TWA: 10 ppm S ⁻	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value
Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls**Engineering Measures**Showers
Eyewash stations

Ventilation systems

Individual protection measures, such as personal protective equipment

Eyeface protection	None required for consumer use. If splashes are likely to occur.: Tight sealing safety goggles.
Skin and body protection	Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eyeface protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES**Physical and Chemical Properties**

Property	Physical state	Appearance	Color	Liquid	Amber	No information available	Odor	Odor Threshold	Sweet	No information available
pH										
Melting / freezing point										
Boiling point / boiling range										
Flash Point										
Evaporation Rate										
Flammability (solid, gas)										
Flammability Limit in Air										
Upper flammability limit										
Lower flammability limit										
Vapor pressure										
Vapor density										
Specific Gravity										
Water Solubility										
Solubility in other solvents										
Partition coefficient: n-octanol/water										
Autoignition temperature										
Decomposition temperature										
Kinematic viscosity										
Dynamic viscosity										
Explosive properties										
Oxidizing properties										

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	No data available

10. STABILITY AND REACTIVITY**Reactivity**

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat. Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information****Inhalation**

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation (based on components). Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.

Eye contact

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation. May cause irritation.

Skin contact

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation. Repeated exposure may cause skin dryness or cracking.

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonia. May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum naphtha, light aromatic 64742-95-5	> 3400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h = 2400 ppm (Rat) 4 h
1,2,4 Trimethylbenzene 95-63-6	> 5000 mg/kg (Rat)	> 3150 mg/kg (Rabbit)	= 16 g/m ³ (Rat) 4 h
Naphtha (petroleum), heavy aromatics 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 560 mg/m ³ (Rat) 4 h
Xylene	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 47635 mg/L (Rat) 4 h = 5000

1330-20-7 1,3,5-Trimethylbenzene 105-67-8	-	-	ppm (Rat) 4 h = 24 g/m ³ (Rat) 4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12000 µL/kg (Rabbit)	-
n-Butylphenyl nitrate 27247-98-7	> 2000 mg/kg (Rat)	> 4800 mg/kg (Rabbit)	> 4.6 mg/L (Rat) 1 h > 14 mg/L (Rat) 4 h
Naphthalene 91-20-3	-	> 20 g/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h

Information on toxicological effects

Symptoms

Erythema (skin redness). May cause redness and tearing of the eyes. Coughing and/or wheezing. Difficulty in breathing. Asthma-like and/or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Mutagenic Effects

There is no data available for this product. Contains a known or suspected mutagen.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7		Group 3		
Cumene 98-82-8		Group 2B		X
n-Butylphenyl nitrate 27247-98-7		Group 2A		X
Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

No information available.

STOT - Single exposure

Respiratory system

STOT - repeated exposure

No information available.

Chronic Toxicity

Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Aspiration may cause pulmonary edema and pneumonitis. May cause adverse effects on the bone marrow and blood-forming system.

Target Organ Effects

Respiratory system. Eyes. Skin. May affect the genetic material in germ cells (sperm and eggs). Gastrointestinal tract (GI). Blood. Central Nervous System (CNS). Kidney. Liver.

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
5,836.00 mg/kg
ATEmix (dermal)
18,250.00 mg/kg (ATE)
ATEmix (inhalation-dust/mist)
4.00 mg/l
ATEmix (inhalation-vapor)
246.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life. Toxic to aquatic life with long lasting effects

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Derivative Range (Water Phase)
Petroleum naphtha, light aromatic 64742-95-5		96h LC50 = 9.22 mg/L (Oncorhynchus mykiss)		48h EC50 = 6.14 mg/L
1,2,4-Trimethylbenzene 95-63-5		96h LC50 = 7.19 - 8.28 mg/L (Pimephales promelas)		48h EC50 = 6.14 mg/L
Naphtha (petroleum), heavy aromatic 64742-94-5	72h EC50 = 2.5 mg/L (Skeletonema costatum)	96h LC50 = 19 mg/L (Pimephales promelas) 96h LC50 = 2.9 mg/L (Oncorhynchus mykiss) 96h LC50 = 1740 mg/L (Lepomis macrochirus) 96h LC50 = 45 mg/L (Pimephales promelas) 96h LC50 = 41 mg/L (Pimephales promelas)		48h EC50 = 0.95 mg/L
Xylene 120-20-7		96h LC50 = 13.4 mg/L (Pimephales promelas) 96h LC50 = 2.65 mg/L (Oncorhynchus mykiss) 96h LC50 = 13.5 - 17.3 mg/L (Oncorhynchus mykiss) 96h LC50 = 13.1 - 16.5 mg/L (Lepomis macrochirus) 96h LC50 = 19 mg/L (Lepomis macrochirus) 96h LC50 = 7.11 - 8.91 mg/L (Lepomis macrochirus) 96h LC50 = 23.53 - 29.97 mg/L (Pimephales promelas) 96h LC50 = 780 mg/L (Cyprinus carpio) 96h LC50 = 780 mg/L (Cyprinus carpio) 96h LC50 = 45 mg/L (Pimephales promelas) (Pimephales promelas)	EC50 = 0.0884 mg/L 24 h	48h EC50 = 3.82 mg/L 48h LC50 = 0.6 mg/L
1,3,5-Trimethylbenzene 106-57-8		96h LC50 = 3.48 mg/L (Pimephales promelas)		24h EC50 = 50 mg/L
Cumene 96-32-8	72h EC50 = 2.6 mg/L (Pseudokirchneriella subcapitata)	96h LC50 = 6.04 - 6.61 mg/L (Pimephales promelas) 96h LC50 = 4.8 mg/L (Oncorhynchus mykiss) 96h LC50 = 2.7 mg/L (Oncorhynchus mykiss) 96h LC50 = 5 mg/L (Pimephales promelas)	EC50 = 0.89 mg/L 5 min EC50 = 1.19 mg/L 15 min EC50 = 1.48 mg/L 30 min EC50 = 172 mg/L 24 h	48h EC50 = 0.6 mg/L 48h EC50 7.9 - 14.1 mg/L
2-Ethylhexyl nitrate 27747-96-7		48h LC50 = 116 mg/L (Salmo gairdneri)	EC50 = 100 mg/L 15 min	
Naphthalene 91-20-3	72h EC50 = 0.4 mg/L (Skeletonema costatum)	96h LC50 = 5.74 - 6.44 mg/L (Pimephales promelas) 96h LC50 = 1.6 mg/L (Oncorhynchus mykiss) 96h LC50 = 0.91 - 2.82 mg/L (Oncorhynchus mykiss) 96h LC50 = 1.39 mg/L (Pimephales promelas) 96h LC50 = 31.0285 mg/L (Lepomis microchirus)	EC50 = 0.93 mg/L 30 min EC50 = 20 mg/L 18 h	48h LC50 = 2.18 mg/L 48h EC50 = 1.96 mg/L 48h EC50 1.09 - 3.4 mg/L

Persistence and Degradability
No information available.

Bioaccumulation

Chemical Name	Log Pow
1,2,4-Trimethylbenzene 95-63-5	3.63
Naphtha (petroleum), heavy aromatic 64742-94-5	6.1
1,2,4-Trimethylbenzene 95-63-5	3.15
Cumene 96-32-8	3.58
2-Ethylhexyl nitrate 27747-96-7	4.14
Naphthalene 91-20-3	3.9

Other adverse effects
No information available.

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal methods**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number U055 U165 U239

Chemical Name	RCRA	RCRA - Basis for Listing Included in waste stream:	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7		F039		U239
Cumene 98-92-8				U055
Naphthalene 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145		U165

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Naphthalene 91-20-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent fillers and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
1,2,4 Trimethylbenzene 95-63-6	Toxic
Xylene 1330-20-7	Toxic Ignitable
Cumene 98-92-8	Toxic Ignitable
Naphthalene 91-20-3	Toxic

14. TRANSPORT INFORMATION

DOT
Proper Shipping Name
Hazard Class

NOT REGULATED
NON REGULATED
N/A

IDG

Not regulated

MEX

Not regulated

ICAO

Not regulated

IATA
Proper Shipping Name
Hazard Class

Not regulated
NON REGULATED
N/A

IMDG/IMO
Hazard Class
Marine Pollutant

Not regulated
N/A
Product is a marine pollutant according to the criteria set by IMDG/IMO

RID

Not regulated

ADR

Not regulated

ADN

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA
DSL
Complies
All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313
Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene - 95-63-6	95-63-6	15 - 40	1.0
Xylene - 1330-20-7	1330-20-7	1 - 5	1.0
Cumene - 98-82-8	98-82-8	1 - 5	1.0
Naphthalene - 91-20-3	91-20-3	0.1 - 1	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard
Chronic Health Hazard
Fire Hazard
Sudden release of pressure hazard
Reactive Hazard
Yes
Yes
Yes
No
No

CWA (Clean Water Act)
This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb			X
Naphthalene 91-20-3	100 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Xylene 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Cumene 98-82-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Naphthalene 91-20-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 0.454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Cumene - 98-82-8	Carcinogen
Naphthalene - 91-20-3	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
1,2,4 Trimethylbenzene 95-63-6	X	X	X	X	X
Xylene 1330-20-7	X	X	X	X	X
1,3,5-Trimethylbenzene 108-67-8	X	X	X		X
Cumene 98-82-8	X	X	X	X	X
Diethyl Benzene 2340-17-4	X				
Naphthalene 91-20-3	X	X	X	X	X

International Regulations**Mexico****National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
1,2,4 Trimethylbenzene 95-63-6 (15 - 40)		Mexico: TWA 25 ppm Mexico: TWA 125 mg/m ³ Mexico: STEL 35 ppm Mexico: STEL 170 mg/m ³
Xylene 1330-20-7 (1 - 5)		Mexico: TWA 100 ppm Mexico: TWA 435 mg/m ³ Mexico: STEL 150 ppm Mexico: STEL 655 mg/m ³
1,3,5-Trimethylbenzene 108-67-8 (1 - 5)		Mexico: TWA 25 ppm Mexico: TWA 125 mg/m ³ Mexico: STEL 35 ppm

Cumene 98-82-8 (1-5)		Mexico: STEL 170 mg/m ³ Mexico: TWA 50 ppm ² Mexico: TWA 245 mg/m ³ Mexico: STEL 75 ppm ² Mexico: STEL 385 mg/m ³
Naphthalene 91-20-3 (0.1-1)		Mexico: TWA 10 ppm ² Mexico: TWA 50 mg/m ³ Mexico: STEL 15 ppm ² Mexico: STEL 75 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada
WHMIS Hazard Class
B3 - Combustible liquid
D2A - Very toxic materials
D2B - Toxic materials



16. OTHER INFORMATION

NFPA	Health Hazards 2	Flammability 2	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 2 *	Flammability 2	Physical Hazard 0	Personal Protection X

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6601
06-May-2015
06-May-2015
No information available

Issuing Date

Revision Date

Revision Note

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet